

# Helmet Communication Units

## HUC5 - Helmet Communication Insert



Coiled cable (Optional)



Left or right side (Optional)



### The Titan Helmet Communication Insert

The HUC5 should be a permanent item for your fire and rescue communication setup when wearing a MSA Gallet F1SF or F2 helmet.

This comprehensive communication device can be directly connected to a speaker microphone or a PTT using the Nexus connection.

The HUC5 comes in a stereo, single and listen only version for your helmet and critical communication needs.

### INDUSTRIES



### COMPATIBLE HELMETS



MSA Gallet F1XF



MSA Gallet F1SF



MSA Gallet F2 X-TREM

### Technical data

Loudspeaker specifications		Cable	
Normal size	40mm, 1,5 inch.	Cable length	55cm
Resonant frequency	530 Hz ± 150 Hz at 1 V	Type	Straight or coiled flame retardant ULV.0
Impedance	8 Ohm ± 15% at 1 KHz 1 V	Connector	Nexus TP120 connector
Sound pressure level	90 dB/w ± 3 dB 0.5 w 50 cm ave at 0.8K, 1K, 1.2K, 1.5K Hz	Microphone	
Response	Fo Hz ~ 6 KHz max 10 dB	Generating element	Electret condenser
Input power	Nominal 0.5 W - Handling capacity 1.0 W	Sensitivity	-33 to -25dB ref 1 Vms (1KHz and 1PA at 1/4)