

Tactical Communication Units

MM50-TAC Remote Speaker Microphone & Control Box



Volume +/- buttons and loudspeaker on/off switch when headset connected.



Side PTT

3.5 mm audio jack for earphone accessories



The MM50-TAC RSM & Control Box

The MM50-TAC is a state-of-the-art high-tech Remote Speaker Microphone. The MM50-TAC can work independently as an RSM with clear transmitting and receiving audio and added features such as emergency button, volume buttons and large push-to-talk buttons.

When the IE2-TAC headset is connected to the MM50-TAC, the MM50-TAC works as a control box, where you can PTT for transmission and use the mode button to adjust the situational awareness volume.

INDUSTRIES



OPTIONS



Use with IE2-TAC Headset

Technical data

Microphone	Omni directional	Environmental specifications	
Sensitivity	-42dB +/- 3dB	Operating temperature	-25° C to +60° C
Speaker	36mm Ø Dynamic	Storage temperature	-40° C to +85° C
Output power	1W Max 1,5W	Mechanical specifications	
Output level	91dB +/- 3dB	Cable flex life	50,000 cycles
Frequency range	580Hz ~ 5KHz	Cable pull strength	Axial 13 kgs
		PTT switch life	100,000 cycles
		Protection rating	IP67